Philips
PAL coax cable

7,5 m

> 75 dB Black

SWV2926W

Ensure a reliable connection

with this PAL coax cable

Depend on this cable to provide you with a reliable audio/video connection between components.

Enjoy good picture quality
- Nickel-plated connectors for reliable contact

Enjoy good audio quality
- High purity copper conductor for reliable signal transfer

Protects against signal loss
- Bare copper shielding

Easy installation
- Non-slip ergonomic grip for easy use

Enjoy extended durability
- Molded plug for secure connections
- Flexible PVC jacket
- Rubber strain relief

PHILIPS

sense and simplicity

PAL coax cable
7,5 m > 75 dB Black

SWV2926W/10

Specifications

Packaging dimensions
- Packaging dimensions (W x H x D): 17.0 x 23.6 x 4.1 cm
- Nett weight: 0.358 kg
- Gross weight: 0.370 kg
- Tare weight: 0.012 kg
- EAN: 87 12581 37999 5
- Number of products included: 1
- Packaging type: Card

Outer Carton
- Outer carton (L x W x H): 57.2 x 26.7 x 17.8 cm
- Nett weight: 4.296 kg
- Gross weight: 5.340 kg
- Tare weight: 1.044 kg
- EAN: 87 12581 38003 8
- Number of consumer packagings: 12

Inner Carton
- Inner carton (L x W x H): 24.9 x 17.8 x 15.2 cm
- Nett weight: 1.432 kg
- Gross weight: 1.510 kg
- Tare weight: 0.078 kg
- EAN: 87 12581 38002 1
- Number of consumer packagings: 4

Product highlights

Bare copper shielding
Bare copper shielding protects against signal loss.

Easy grip
This non-slip grip makes connecting your components easy and ergonomically comfortable.

Flexible PVC Jacket
Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

High purity copper
This copper conductor provides high accuracy in signal transfer with minimal resistance.

Molded plug
Molded plugs ensure secure connections between components and offer extended durability.

Nickel-plated connectors
Nickel-plated connectors establish a clean contact between the cable and connector for a reliable connection.

Rubber strain relief
Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.

Issue date 2008-10-28
Version: 1.1.7
12 NC: 8670 000 35452
EAN: 87 12581 37999 5

© 2008 Koninklijke Philips Electronics N.V.
All Rights reserved.
Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com